

PRODUCT DATASHEET DST MITW 15 W/6500 220...240 V B22d

OSRAM DULUXSTAR MINI TWIST | Compact fluorescent integrated, spiral shape



AREAS OF APPLICATION

- General illumination
- Domestic applications
- Wherever compact and efficient lamps are needed
- Wherever cold light colors are needed
- Outdoor use in enclosed and ventilated luminaires only

PRODUCT BENEFITS

- Fast return on investment
- Compact dimensions
- Up to 80 % less energy consumption compared with ordinary light bulbs

PRODUCT FEATURES

- Available in 2 light colors: 827 and 865
- Also available in activating light color LUMILUX Cool Daylight
- Average life: up to 8,000 h



TECHNICAL DATA


Electrical data

| Nominal wattage | 15.00 W |
|---------------------|----------|
| Rated wattage | 15.00 W |
| Nominal voltage | 220240 V |
| Nominal current | 0.15 A |
| Operating frequency | 5060 Hz |

Photometrical data

| Nominal luminous flux | 900 lm |
|--------------------------|--------|
| Rated luminous flux | 900 lm |
| Rated color temperature | 6500 K |
| Light color | 6500 |
| Color rendering index Ra | ≥80 |
| Color temperature | 6500 K |
| Luminous flux | 900 lm |
| Color rendering index Ra | ≥80 |

Dimensions & weight



| Overall length | 105.0 mm |
|----------------|----------|
| Product weight | 55.00 g |
| Length | 105.0 mm |

Lifespan

| Nominal lamp life time | 10000 h |
|------------------------|---------|
| Rated lamp life time | 10000 h |

Additional product data

| Base (standard designation) | B22d |
|-----------------------------|------|
|-----------------------------|------|

PRODUCT DATASHEET

| Mercury content | 2.0 mg |
|-----------------|--------|
| Show WEEE picto | Yes |

Certificates & standards

Cleaning instruction in case of breakage

What to do if a lamp containing mercury breaks?

SAFETY ADVICE

In case of lamp breakage: www.ledvance.com/brokenlamp Not for use with external dimmers or electronic switches.

LOGISTICAL DATA

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-------------------------------------|---------------------------------|---|----------------------|--------------|
| 4052899109377 | DST MITW 15 W/6500 220240 V B22d | Shipping carton box 12 | 268 mm x 94 mm x 131 mm | 3.30 dm ³ | 880.00 g |
| 4052899146341 | DST MITW 15 W/6500 220240 V B22d | Shipping carton box 20 | 229 mm x 187 mm x 143 mm | 6.12 dm³ | 1498.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.