



Rack PDU,Basic, Zero U, 16A, 230V, (20) C13 & (4) C19, IEC C20

AP7552

Overview

Lead time Usually in Stock

Main

Colour	Black	
Product or component type	PDU	
PDU type	Basic	
Cord length	3.05 m	
Number of cables	1	
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit	

Complementary

Input Voltage	200 V	
	208 V	
	230 V	
Height	161.9 cm	
Width	5.6 cm	
Output Voltage	230 V	
Depth	4.4 cm	
Net weight	4.86 kg	
Mounting location	0:1	
Mounting location	Side	
Mounting preference	No preference	
mounting preference	No preference	
Input Plug Type	IEC 60320 C20	
	120 00020 020	
Mounting mode	Rack-mounted	
	Tidot Hourist	
Rack units	0U	
Mounting position	Vertical	
Input current limits	16 A	
Load capacity	3680 VA	
-		
Network frequency	50/60 Hz	
Outlet type and quantity	20 IEC 60320 C13	
Sauce type and quantity	4 IEC 60320 C19	
	4 150 00320 0 19	

Environment

Product certifications	CE GOST IRAM VDE	
Ambient air temperature for operation	045 °C	
Relative humidity	595 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-2565 °C	
Storage Relative Humidity	595 %	
Storage altitude	0.000000000015240.000000000 m	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	212.1 cm
Package 1 Width	15.2 cm
Package 1 Length	12.7 cm
Package 1 Weight	5.758 kg

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	120
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
[™] Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Product contains halogen above thresholds
Take-back	Yes