

Specifications





Power Cord Kit (6 ea), Locking, C13 TO C14 (90 Degree), 0.6m

AP8702R-WW

Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Lead time	Usually in Stock

Main

Product or component type	Power cord
Input Connection Type	IEC 60320 C14
Cable length	0.6 m
Number of cables	6
Provided equipment	3 left-angle jumper cords 3 right-angle jumper cords

Physical

Colour	Black
Height	24 cm
Width	7 cm
Depth	4 cm
Net weight	0.7 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input	
Max line current	10 A
Input current limits	10 A

Output

Max current draw	10 A
Number of power socket outlets	1 IEC 60320 C13
Power cable length	0.6 m

Conformance

Product certifications	CCC	
	PSE	
	VDE	

Environmental

Ambient air temperature for operation	070 °C
Relative humidity	2080 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2575 °C
Storage Relative Humidity	2080 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24 cm
Package 1 Width	4 cm
Package 1 Length	7 cm
Package 1 Weight	0.7 kg

Contractual warranty

Warranty

2 years repair or replace

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained $>$	
How we assess product sustainability \geq	
Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	220
Environmental Disclosure	Product Environmental Profile
Use Better	
In the second secon	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Use Again	
$^{\circlearrowright}$ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Yes