



Power Cord, Locking C19 to Australia Plug, 3.0m

AP8754

Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
I ead time	Lleually in Stock

Main

Product or component type	Power cord
Main Output Voltage	240 V
Cable length	3.00 m
Number of cables	1

Physical

Colour	Black
Height	23 cm
Width	23 cm
Depth	4.5 cm
Net weight	0.42 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Plug standard	Australian/Chinese
Max line current	15 A
Input current limits	15 A

Output

Max current draw	15 A
Number of power socket outlets	1 IEC 60320 C19
Power cable length	3.05 m

Environmental

Ambient air temperature for	075 °C
operation	

Relative humidity	2080 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2575 °C
Storage Relative Humidity	2080 %
Storage altitude	0.000000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23 cm
Package 1 Width	4.5 cm
Package 1 Length	23 cm
Package 1 Weight	0.42 kg
SCC14	10731304279782

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

<i>a</i>			
Environmental footprint	footprint	Environmenta	0

Environmental Disclosure Product Environmental Profile

Use Better

Materials and Substances EU RoHS Directive Compliant REACh Regulation REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Yes