



Usually in Stock

CD with software Telephone cable User manual

Back-UPS

APC Power-Saving Back-UPS, Back-UPS, ES 550VA, 230V, 8 Australian (AS 3112) outlets (4 surge)

BE550G-AZ

Overview

Lead time

Main	
Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	330 W
Rated power in VA	550 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	Australian/Chinese
output connection type	4 Australian surge 4 Australian
Cable length	1.8 m
Battery type	Lead-acid hattery

Batteries & Runtime

Provided equipment

Range of product

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Battery charger power	5 W rated
Battery power in VAH	86 VAh runtime
Battery life	35 year(s)
Replacement battery	APCRBC110 ☐
Extended runtime	0

General

Number of power module free

slots

Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	8.8 cm
Width	18 cm
Depth	30.2 cm
Net weight	5.5 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

Input

Network frequency	50/60 Hz
Plug standard	Australian/Chinese
Maximum input current	10 A

Output

Maximum configurable power in W	330 W
Output frequency	4763 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Output voltage tolerance	+/- 5% static and 100% load step
Maximum configurable power in VA	550 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	A-Tick C-Tick CE Telepermit
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	030000 ft
Ambient air temperature for storage	-1540 °C
Storage Relative Humidity	095 %

Storage altitude	0.00000000009144.0000000000 m
Acoustic level	40 dBA

Communications & Management

Control panel LED status display with on line : on battery : replace battery and overload indicators

Surge Protection and Filtering

Surge energy rate	310 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.8 cm
Package 1 Width	39.3 cm
Package 1 Length	23.5 cm
Package 1 Weight	6.2 kg
SCC14	10731304275418
Pallet unit layers	20
Pallet layers	4

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint

Environmental Disclosure

Optimized Energy Efficiency

Product Environmental Profile

Energy efficient product

Use Better

EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
[⋯] Energy efficiency	

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes