



Usually in Stock

APC Back-UPS, Back-UPS, 650VA, Tower, 230V, 4 IEC C13 Outlets, User Replaceable Battery

BK650-AS

Overview

Lead time

Battery type

Main	
Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	400 W
Rated power in VA	650 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
output connection type	3 IEC 60320 C13 1 IEC 60320 C13 surge
Cable length	1.8 m
Number of cables	2

Lead-acid battery Provided equipment CD with software

Documentation CD 1 x detachable 1.2 m IEC power cord

1 x detachable 1.8 m IEC power cord Telephone cable

USB cable Warranty card

Range of product Back-UPS

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	1
Battery charger power	12 W rated
Battery power in VAH	95 VAh runtime
Battery life	46 year(s)
Replacement battery	RBC17 ☐

Extended runtime 0

General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

•	
Colour	Beige
Height	16.5 cm
Width	9.1 cm
Depth	28.4 cm
Net weight	6.04 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Input voltage limits	160282 V adjustable 180260 V

Output

Maximum configurable power in W	400 W	
UPS type	Standby	
Wave type	Stepped approximation to a sinewave	
Maximum configurable power in VA	650 VA	

Conformance

Product certifications	A-Tick C-Tick CE GOST NEMKO
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	595 %
Operating altitude	030000 ft
Ambient air temperature for storage	-1545 °C

Storage Relative Humidity	595 % 0.00000000004572.0000000000 m	
Storage altitude		
Acoustic level	45 dBA	
Heat dissipation	0 Btu/h	

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate 320 .

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	49.4 cm
Package 1 Width	41.5 cm
Package 1 Length	18.5 cm
Package 1 Weight	7.32 kg
SCC14	10731304224430

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

∅ Environmental footprint

Environmental Disclosure

Optimized Energy Efficiency

Product Environmental Profile

Energy efficient product

Use Better

EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
[⋯] Energy efficiency	

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes