Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





APC SERVICE BYPASS PDU, 230V 10AMP W/ (6) IEC C13

SBP1500RMI

Overview

Lead time	Usually in Stock

Main

Main Input Voltage	230 V	
Product or component type	Bypass kit	
Main Output Voltage	230 V	
Input Connection Type	IEC 60320 C14	
Number of rack unit	2U	
Cable length	2.0 m	
Number of cables	1	
Provided equipment	User manual Rack mounting brackets	
Range of product	Maintenance Bypass Panels	

Physical

Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	7.6 cm
Net weight	2 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Network frequency	50/60 Hz
Permissible voltage	220240 V
Max line current	10 A
Input current limits	10 A
Load capacity	1500 VA
Power factor	01

Output

Max current draw	10 A	
Number of power socket outlets	6 IEC 60320 C13 1 IEC Jumpers	
Number of power socket outlets	6	
Protection type	Circuit breaker	
Power cable length	1.2 m	
Efficiency	99 %	

Conformance

Product certifications	VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	015000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	0.000000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.1 cm
Package 1 Width	46.3 cm
Package 1 Length	29.5 cm
Package 1 Weight	3.5 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	56
Package 2 Height	113 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	195.608 kg

Contractual warranty

Warranty 2	e years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
Use Again	

Use Again

○ Repack and remanufacture	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No