Product datasheet

Specifications

APC



APC Smart-UPS VT Maintenance Bypass Panel 10-20kVA 400V Wallmount

SBPSU10K20HC1M1-WP

Overview

Lead time

Usually Ships within 4 Weeks

Main

Main Input Voltage	400 V 3 phases
Main Output Voltage	400 V 3 phases
Number of cables	1
Provided equipment	Installation guide User manual

Physical

-		
Colour	Black	
Height	31.5 cm	
Width	30.5 cm	
Depth	17.5 cm	
Net weight	7.01 kg	
Mounting location	Front	
Mounting preference	No preference	
Mounting mode	Not rack-mountable	

Input

Network frequency

50 Hz +/- 3 Hz

Conformance Standards EN 50091-2 FN/JEC 62040-3

Standards	EN 50091-2
	EN/IEC 62040-3
	EN/IEC 62040-1-1

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	050000 ft
Ambient air temperature for storage	040 °C
Storage Relative Humidity	095 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	44.2 cm
Package 1 Width	25.4 cm
Package 1 Length	38.1 cm
Package 1 Weight	7.73 kg
Number of Units in Package 3	1

Contractual warranty

Warranty

1 year (parts only)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

Use Again

♡ Repack and remanufacture		
Removable battery	User replaceable	
Take-back	No	