



Main

Range	PowerLogic
Product name	PowerLogic PM5000
Device short name	PM5330
Product or component type	Power meter

Complementary

Power quality analysis	Up to the 31st harmonic
Device application	Power monitoring Multi-tariff
Type of measurement	Voltage Current Frequency Power factor Energy Active and reactive power
[Us] rated supply voltage	100...415 V AC (45...65 Hz) 125...250 V DC
Network frequency	50 Hz 60 Hz
[In] rated current	1 A 5 A
Poles description	1P + N 3P 3P + N
Power consumption in VA	<= 10 VA at 415 V
Ride-through time	80 ms 120 V AC typical 100 ms 230 V AC typical 100 ms 415 V AC typical
Display type	Backlit LCD
Display resolution	128 x 128 pixels
Sampling rate	64 samples/cycle
Measurement current	10...9000 mA
Analogue input type	Current (impedance 0.3 mOhm) Voltage (impedance 5 MOhm)
Measurement voltage	35...690 V AC 45...65 Hz between phases 20...400 V AC 45...65 Hz between phase and neutral
Frequency measurement range	45...65 Hz
Number of inputs	2 digital
Measurement accuracy	+/- 0.5 % active energy +/- 2 % reactive energy +/- 0.5 % active power +/- 0.5 % apparent power +/- 0.05 % frequency +/- 0.005 % power factor +/- 0.5 % current +/- 0.5 % voltage
Accuracy class	Class 0.5S (active energy according to IEC 62053-22)
Number of outputs	2 digital

	2 relay
Information displayed	Tariff 4
Communication port protocol	Modbus RTU and ASCII 2 wires, : 9.6, 19.2 and 38.4 kbauds, even/odd or none, insulation: 2500 V JBUS
Communication port support	RS485
Data recording	Data logs Event logs Min/max of instantaneous values Time stamping Alarm logs Maintenance logs
Memory capacity	256 kB
Connections - terminals	Voltage circuit: 4 screw terminal block Control circuit: 2 screw terminal block Current transformer: 6 screw terminal block Input/output circuit: 6 screw terminal block Relay output: 4 screw terminal block Ethernet network: RJ45 connector
Mounting mode	Flush-mounted
Mounting support	Framework
Standards	IEC 60529 IEC 61557-12 IEC 62053-22 EN 50470-1 EN 50470-3 UL 61010-1 IEC 62053-24
Product certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1
Width	96 mm
Depth	72 mm
Height	96 mm
Product weight	430 g

Environment

electromagnetic compatibility	<ul style="list-style-type: none"> conducted and radiated emissions class class B, conforming to EN 55022 limits for harmonic current emissions class class A, conforming to IEC 61000-3-2 electrostatic discharge class level 4, conforming to IEC 61000-4-2 conducted RF disturbances class level 3, conforming to IEC 61000-4-6 magnetic field at power frequency class level 4, conforming to IEC 61000-4-8
IP degree of protection	IP52 (front) conforming to IEC 60529 IP30 (body) conforming to IEC 60529
relative humidity	5...95 % 50 °C
pollution degree	2
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-40...85 °C
operating altitude	2000 m

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1321 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available