

COMMUNICATION CABLES – Telephone Cables

CONNECTING WIRE



Cable description:

Solid PACW, PVC Insulated, Max Resist 94.5, Capacitance Unbalance max 300/500m @ 800hz.

Code	Description	Number of wires	Overall diameter mm	No./Dia. wire mm	Max. pulling tension N	Mass kg/km	Telstra Version for Approved Contractors Telstra Part No.
CJMP2RDWH	Red-White	2 PACW	1.8	1/0.50	38	4.5	003/00250
CJMP2GRWH	Green-White	2 PACW	1.8	1/0.50	38	4.5	003/00249

Guide for codes – Coax & connecting wire:

Product: C = Coax or Connecting Wire
 Code or Cable Type: CJMP (Refer relevant page for codes and product description.
 (e.g. CJMP = Connecting wire jumper)
 Optional: Colour: RDWH = Red White
 BLWH = Blue White
 GNWH = Green White

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

Prysmian Cables & Systems Australia Pty Ltd

1 Heathcote Road, Liverpool 2170 NSW, Australia
 Ph: 1300 300 304 Fx: 1300 300 307
 E-mail: sales.au@prysmiangroup.com

www.prysmiancable.com.au

