

Data Sheet

Triscan 3-Wire Sensor

CAT NO. **488TRI3W**



Cat No	488TRI3W
Description	3 Wire Sensor
Supply voltage	230-240V a.c.
Min/Max load	0VA – 2400VA
Detection method	Passive infrared, microwave and photoelectric sensor
Detection angle	120°
Lux adjustment	10 Lux to full sun
Time on adjustment	8 seconds to 15 minutes
Head swivel	120°
IP rating	IP66
Colour	White (WE)
Operating temperature	0° to 40°C
Mounting	Fits standard 84mm mounting block (included)
Mounting height	1.8 – 2.4 metres

Triscan 3-Wire Sensor

CAT NO. **488TRI3W**



Single product			
Cat No	Dimensions	Barcode	Weight
488TRI3W	90mmW x 145mmH x 135mmD	9321001432753	0.365kg

Outer box (QTY 20)			
Cat No	Dimensions	Barcode	Weight
488TRI3W	300mmW x 290mmH x 500mmD	9321001432760	8.2kg

- Accurate detection with 3-in-1 passive infrared (PIR), microwave and photoelectric sensors
- Weatherproof IP66 rating suitable for harsh environments
- Long lasting device backed up by 5 year warranty
- 18 meter detection range
- 120° detection angle
- Built-in wiring not accessible from the outside
- Adjustable time delay
- Adjustable LUX level
- With mounting block and gasket supplied

HPM Legrand - AUS
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

HPM Legrand - NZ
0800 476 009
www.legrand.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or HPM Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.