# MECHANICAL FITTINGS

## PA, PC & BCST SERIES





### PA & PC SERIES

Wedge type strain clamps

- + PA series for higher tensions.
- + PC series for service tensions.
- + PC series suitable for 2, 3v and 4 core twisted cables.
- + Stainless steel bails on PA and PC models.
- + Fibreglass reinforced UV stabilised
- + Stainless steel bails
- + Fibreglass reinforced UV stabilised nylon.

Product Number	Cable Type	Cable Diameter (mm)	No. and Size of Cores (mm²)	Min. Failing Load (kN)	Pack Size
PC63R22	Neutral Screened	14 to 22		2.5	10
PC63F27	Twisted or Flat		2 x 6 to 4 x 35	2.5	100
PC63F27A	Twisted or Flat		2 x 6 to 4 x 35	2.5	100
PC63F27B	Twisted or Flat		2 x 6 to 4 x 35	2.5	100
PA4	Twisted or Flat		2 x 6 to 2 x 25	6	10
PA5	Twisted or Flat		2 x 25 to 2 x 50	14	10
PA5D	Twisted or Flat		2 x 16 to 4 x 25	12	10













BCST-2025-3G

BCST-4035-3G

BCST-2025-3P

BCST-2025-3PA

BCST-4035-3P

BCST-4035-3PA

#### **BCST SERIES**

Bolted Type Service Strain Clamps

- + Nylon glass reinforced clamping blocks
- + Blocks spring loaded for ease of cable mounting
- + Galvanised steel or plastic strap
- + M10 stainless steel fastening hardware
- + Can also be used as a suspension fitting by rotating the clamping blocks 90 degrees

Product Number	Cable Size (mm²)	Strap	Hook Style	Pack Size
BCST-2025-3G	2 x 10 to 35	Galvanised	Open	50
BCST-4035-3G	4 x 10 to 35	Galvanised	Open	30
BCST-2025-3P	2 x 10 to 35	Nylon	Open	50
BCST-2025-3PA	2 x 10 to 35	Nylon	Closed	50
BCST-4035-3P	4 x 10 to 35	Nylon	Open	30
BCST-4035-3PA	4 x 10 to 35	Nylon	Closed	30