

Catalogue No: **440G-LZS21SPLH**

GUARD LOCK SWITCH POWER TO LOCK STND-ACT 8-PIN-MICRO-QD

Safety > Safety Interlocks > Mechanical Interlocks > Allen-Bradley 440G GuardLocking Switches > 440G-LZ



440G-LZ guard locking safety switch, power to lock, standard code, 8-pin DC Micro (M12) connector

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Safety Switch Type	Guard Locking Switch type
Interlock Type	Power to Lock type
Number of Safety Contacts	2 qty safety
Output Configuration, Safety	2 NC
Number of Aux Contacts	1
Output Configuration, Auxiliary	1 NO
Holding Force, Max	1300 N
Connection / Termination	M12 x 1, DC Micro, 8-pin with pigtail
Actuator Included	Yes Y / N
Un, Nominal Operational Voltage, DC	24 V DC
Material, Body / Housing	ABS material
Operating Temperature, Max	55 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	55 °C max
Storage Temperature, Min	-25 °C min
IP Rating	IP66 IP67 IP69K
Height	50 mm
Depth	140 mm
Width	45 mm
Weight	0.4 kg
Shock Acceleration (Max.)	30 g
Shock Duration (Max.)	11 ms
Shock Rating	IEC 60068-2-27
Vibration Frequency, Operational (Max.)	55 Hz
Vibration Rating	IEC 60068-2-6

Catalogue No: **440G-LZS21SPLH**

GUARD LOCK SWITCH POWER TO LOCK STND-ACT 8-PIN-MICRO-QD

Safety > Safety Interlocks > Mechanical Interlocks > Allen-Bradley 440G GuardLocking Switches > 440G-LZ



Standards Compliance	UL 508 IEC 60947-5-1 IEC/EN 61508 SIL1 IEC/EN 61508 SIL2 IEC/EN 61508 SIL3 IEC/EN 62061 SILCL1 IEC/EN 62061 SILCL2 IEC/EN 62061 SILCL3 EN 954 / ISO 13849:1999 Category 1
Certifications	CE C-UL-US C-Tick

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-