

TMC2AQ2V

cartridge M221 - 2 analog voltage outputs - I/O extension



Main

Range of product	Modicon M221
Product or component type	Analogue output cartridge
Product compatibility	Modicon M221C

Complementary

Analogue output number	2
Analogue output type	Voltage (0...10 V)
Analogue output resolution	12 bits
LSB value	2.44 mV voltage, output range: 0...10 V
Load type	Resistive
Load impedance ohmic	$\geq 2 \text{ k}\Omega$
Conversion time	20 ms
Stabilisation time	40 ms
Absolute accuracy error	+/- 0.3 % of full scale 25 °C +/- 1 % of full scale
Temperature drift	+/- 0.02 %FS/°C
Repeat accuracy	+/- 0.4 %FS
Non-linearity	+/- 0.01 %FS
Cross talk	$\leq 1 \text{ LSB}$
Type of cable	Twisted shielded pairs cable
Electrical connection	2 screw terminal blocks (pitch 3.81 mm) 1.5 mm ² 3 for outputs
Cable distance between devices	Twisted shielded pairs cable: 30 m for output
Insulation	Non-insulated between analogue output and internal logic
Height	41 mm
Depth	15 mm
Width	35 mm
Product weight	0.015 kg

Environment

immunity to microbreaks	10 ms
-------------------------	-------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1415 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.