

# TMC2CONV01

cartridge M221 - conveying 1 serial line - I/O extension



## Main

Range of product	Modicon M221
Product or component type	Serial line cartridge
Product compatibility	Modicon M221C
Product specific application	Conveying applications

## Complementary

Integrated connection type	Non isolated serial link for screw terminal block (RS232) Non isolated serial link for screw terminal block (RS485)
Transmission rate	1.2...115.2 kbit/s (115.2 kbit/s by default), bus length = 15 m (RS485) 1.2...115.2 kbit/s (115.2 kbit/s by default), bus length = 3 m (RS232)
Communication port protocol	Modbus non isolated serial link for master/slave (RTU/ASCII or SoMachine-Network)
Insulation	Non-insulated between lines and internal logic
Height	41 mm
Depth	15 mm
Width	35 mm
Product weight	0.015 kg

## Environment

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1415 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.