

## CLEVERTRONICS LP PREMIUM SURFACE MOUNT SWINGBLADE LED EXIT



### PRODUCT INFORMATION

Catalogue Number	CSBLED
Description	LED LP PREMIUM Swingblade Exit, 24 metre viewing Distance
Construction	Metal Frame, White End Caps with Acrylic & Polycarbonate Diffuser
Mounting	Surface Mount, Wall or Ceiling on a slide connect bracket – Single & Double Sided “NOTE: If product is suspended below the ceiling or mounted on a metal surface the Swingblade bracket cover plate accessory (P/N:2740100) is required to cover the mains terminals.”
Dimensions L x W x H	See Images above
Operating Mode	Maintained
Testing System	Manual Test Switch
Charging Method	Intelligent current limited constant voltage charger
Diffuser	(All directional inserts included in the box)
Lamp(s)	24 x high intensity, low energy LED, surface mounted onto a replaceable lamp bar - 100,000hour
Operating Voltage	240V
Power Consumption	3.5W (standby) 6.2W (max during 16 hour charge)
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZ2293 Classification	C <sub>0</sub> =D6.3 C <sub>90</sub> =E3.2

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550070	Battery: 3.2Volt, 3200mAh Li-ion
8002355	PCA: Lithium S/BLADE Driver. #CT10164-L4
8002185	PCA: 24DLED SB LED Strip, #CT10156-D2

