Data Sheet

Weatherproof Programmable Light Sensitive Switch IP56, 10A



CAT. NO. **PE170R2**



Cat. No.	PE170R2	
Description	Weatherproof Programmable Light Sensitive Switch	
Operation	Turn lights on at sunset and turns lights off at user-specified time. (Off-time is the actual time desired rather than a calculated sunset + delay time)	
Contacts	Normally open	
Colour	Grey base with opalescent cover	
Supply voltage	230 - 240 Va.c. ± 6%	
Frequency	50 Hz	
Connection type	3 wires	
Maximum load	2400W Incandescent 2400W Halogen 1000VA Compact Fluorescent 1000W LED 500VA High intensity discharge 1500VA Fluorescent tube	
Minimum load	5W	
Lux level adjustment	5 – 2000Lux	
Off time adjustment	From 9pm to 4am in increments of 30 minutes or dawn (light dependent)	
Stand-by power consumption at V _{in}	V in ≤1 W	
Operating temperature	0° to 50° C	
Unit size	83mm W x 83mm H x 56mm D	

Weatherproof Programmable Light Sensitive Switch IP56, 10A

CAT NO. **PE170R2**





FEATURES

- Suitable for all commercial and residential applications.
- Weatherproof rating IP56.
- Multiple side and back cable entries: Ø 25mm
- Low standby power consumption < 1W
- Programmable Off time.
- Programmable Lux setting. (On time)
- Energy efficient unique algorithm to turn off lights at a specific time.
- Non-volatile memory ensures program is restored in case of power loss.
- Surface mount.
- Easy to program.
- Easy to install.

Single product		
Cat. No.	Dimensions	Barcode
PE170R2	88 W x 72 H x 115 Dmm	9321001432821

Outer box (QTY 60)		
Cat. No.	Dimensions	Barcode
PE170R2	397 W x 375 H x 390 Dmm	9321001432838

Legrand - Australia 1300 369 777 www.hpm.com.au ABN 31 000 102 661