

Data Sheet

Power Converter 10 to 15A

CAT NO. REPC11015



Product specifications	
Cat No	REPC11015
Supply voltage	230-240V a.c. 50Hz
Max load	2400V (10A)
Plug	10A, fully moulded
Outlet	15A
Rated residual current	30mA
Typical trip time	30ms
Lead	1.0mm flexible heavy duty (10A) - 1.8m with parking clip
RCBO	Type AC
Rated	Indoor use only

Power Converter 10 to 15A

CAT NO. REPC11015



- Ideal for providing temporary mains supply to 15A appliances and power tools requiring power for short durations
- Adapts 10A connection to 15A connection
- 1 x 15A Double pole shuttered outlet for extra safety
- Parking clip to prevent lead unravelling
- Not suitable for use on dedicated, permanently connected caravan sites or construction sites
- RCBO (10A) protection - combines Residual Current Device (RCD), for fast power cut off reducing the risk of electrocution and Miniature Circuit Breaker (MCB) for overload protection

Single product		
Dimensions	Barcode	Weight
150(L) x 134(W) x 189(H)mm	9321001435013	1125g

Outer box (Qty 9)		
Dimensions	Barcode	Weight
470(L) x 420(W) x 220(H)mm	9321001435020	10.1kg

Refer to your group buying office, HPM Legrand Sales Representative or HPM Legrand Sales Office for pricing.

HPM Legrand - AUS
1300 369 777
www.hpm.com.au
ABN 31 000 102 661

Please note: specifications are subject to change without prior notice.