





BLADE

BLADE40W12SM-6K

SAP CODE: 2000076



Photometric Diagram



Unit: cd
 - C0/180 120.0deg
 - C90/270 120.0deg

1200mm, 6000K, Slim profile LED batten

A sleek and modern LED batten that produces strong illumination.

Accessories
SUSPENSION KIT

KEY INFORMATION

Lumen Output	3770lm
Input Power	40W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	Non-Dimmable
Trim Colour	WHITE
Warranty	5yr
IP Rating	IP20
IK Rating	N/A
IC Rating	N/A
Rebate Scheme Approvals	VEET; REES; IPART LCP 40

PHOTOMETRIC

Efficacy	94lm/W
LED	SMD
CCT	6000K
CRI	>80
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	70-90VDC
Power Factor	>0.9
LED Input Current (nominal)	480mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Bracket
Connection Type	Terminal Block PA12
Total Weight	0.66kg
Dimensions	1215x100x30mm
Operating Ambient Temp.	-25 to 50°C
Electrical Classification	Class 2
Food Grade Approval	HACCP