

CLEVERTRONICS LP LIFELIGHT, BLACK



PRODUCT INFORMATION

Part Number	CLIFE-BLK
Description	LP Premium Lifelight, high performance, recessed Emergency Light, Enabled with Clevertest Plus, Black
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single mint LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 3.9 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
CLIFE-CKIT	Lifelight, Control Only, LP Lithium
1100935	Lifelight Head Assembly, Round, 1LED, Black

