

ML-F20-MULTI



## **Technical information**

Total power consumed: 20W\*

Lumen output W|NW|WW: 1920lm | 2000lm | 1900lm Colour temperature W|NW|WW: 6000K | 4000K | 3000K

CRI: 80+

Efficacy: 95-100lm/W

IP rating: IP20

Beam angle: 120 degrees

Dimmable: Yes

Average life: 30,000 hrs\*\*

Operating temperature: -20° to +45°C

Warranty: 3 years / 5 years for PLI (lodge online)
Length: 600 mm | Width: 120 mm | Height: 46 mm

Weight: 1.23kg

\*Total power consumed including driver

\*\*Life span is calculated on expected average life of LED chips





## **Technical information**

Total power consumed: 40W\*

Lumen output W|NW|WW: 4040lm | 4200lm | 4000lm Colour temperature W|NW|WW: 6000K | 4000K | 3000K

CRI: **80+** 

Efficacy: 100-105lm/W

IP rating: IP20

Beam angle: 120 degrees

Dimmable: Yes

Average life: 30,000 hrs\*\*

\*Total power consumed including driver

Operating temperature: -20° to +45°C

Warranty: 3 years / 5 years for PLI (lodge online)

Length: 1200 mm | Width: 120 mm | Height: 46 mm

Weight: 2.8kg

\*\*Life span is calculated on expected average life of LED chips

M-Elec has combined both design and function together to produce the new F20-MULTI and F40-MULTI. The designer slimline LED battens are dimmable, boast a high lumen output and have an excellent efficacy.

Following on from other M-Elec 'MULTI' fittings, the new F20-MULTI and F40-MULTI feature a SELECTOR switch, which allows the installer to choose between white, neutral white and warm white colour outputs at the time of installation.

With its adaptable body design, this LED batten allows continuous runs, suspension applications and surface mount installations.



## **SELECTABLE** color output!

- ▶ White
- ▶ Neutral White
- ▶ Warm White









