



Switch Board

Standoff Insulators

- 660 Volts Rated
- Compression moulded
- Glass Re-enforced Polyester Material
- High Dielectric Strength
- Arc Quenching and Non-tracking
- Quality Finish and Appearance
- Non Flammable
- Wear and Corrosion Resistant
- High Mechanical Strength
- Dimensional Stability
- Moulded In Brass Inserts
- Metric Thread Sizes



Part Number	Stud Size (mm)	Overall Height H (mm)	Diameter W (mm)	Pack Qty
SOIRED25M6	6	25	30	50
SOIRED35M8	8	35	40	25
SOIRED35M10	10	35	40	25
SOIRED40M8	8	40	40	24
SOIRED40M10	10	40	40	24
SOIRED50M8	8	50	50	10
SOIRED50M10	10	50	50	10
SOIRED50M12	12	50	50	10
SOIRED60M10	10	60	55	20
SOIRED60M12	12	60	55	20
SOIRED76M10	10	76	60	20

Din Rail

- Pacified Steel & Aluminium available



Part Number (Slotted Pacified Steel)	Depth (mm)	Length (mm)	Pack Size	Box Size
DR37404	7	2000	20	60
DRD37404	15	2000	20	60
Part Number (Plain Pacified Steel)				
DRP37404	7	2000	20	60
DRDP37404	15	2000	20	60
Part Number (Slotted Aluminium)				
DRA37404	7	2000	20	60