

## PREMIUM Exit and Emergency Luminaires

### Classic Lithium Exit

Body and Diffuser sold separately.

A modular, user-friendly exit luminaire that is easily switchable between maintained and non-maintained modes of operation. The body remains the same, for both wall mounted and ceiling mounted diffuser configurations.



LiFePO<sub>4</sub> WER™

#### Features and Benefits

- Sentinel Automatic Self-testing built-in as standard
- LED technology for bright consistent & efficient light distribution
- Lithium Iron Phosphate battery including integrated battery management system (BMS) to maximize battery life.
- Wall or Ceiling Mountable
- Maintained / Non-maintained mode of operation
- Designed and manufactured in accordance to AS/NZS 2293



MLELDP (Body and Diffuser sold separately)		
<b>Input</b>	<b>Operating Voltage</b>	230V
	<b>Frequency</b>	50Hz
<b>Output</b>	<b>LED Array</b>	6x 0.5W Everlight LEDs
	<b>Light Source</b>	2W
	<b>Function</b>	Multi-mode
	<b>Power Consumption (LEDs)</b>	5.5W
<b>Battery</b>	<b>Type</b>	LiFePO <sub>4</sub>
	<b>Charger</b>	Variable current CV
	<b>Protection</b>	Overcharge and low voltage disconnect
	<b>Emergency Runtime</b>	2 hours*
<b>Physical</b>	<b>IP Classification</b>	IP20
	<b>Weight</b>	1.5kg
	<b>Dimensions (LxWxH)</b>	385x155x90mm (Body only)
	<b>Construction</b>	Glass-filled ABS
<b>Installation</b>	<b>Mounting</b>	Surface. Wall or Ceiling.
<b>Environment</b>	<b>Temperature</b>	0°C - 40°C
	<b>Relative Humidity</b>	0 - 95%
<b>Conformance</b>	<b>Standards</b>	AS/NZS 2293 / EMC
<b>Intelligence</b>	<b>Sentinel</b>	In-built
	<b>WiNetRF</b>	Compatible
<b>Warranty</b>	<b>Duration</b>	Fitting: 5 Years / Battery: 1 Year

\*Guaranteed to meet runtime requirements of AS/NZ 2293 throughout warranty duration.

ACCESSORY	DESCRIPTION
BEL-DRX	Wall mount diffuser c/w decal pack
BEL-DTX	Ceiling mount diffuser c/w decal pack
BEL-D50A	Wall/ceiling mount translucent diffuser
BEL-901874	Wall mount wire guard
BEL-901888	Ceiling mount wire guard
BEL-31511	Replacement battery

\*Exits are shipped out in maintained mode & with Sentinel option deactivated. Refer to manual for activation.

\*Diffuser & body sold separately.

SPACING TABLE	MOUNTING HEIGHT (m)			
NATA Classification	2.1	2.4	2.7	3.0
<b>MLEDLP + DRX Diffuser (Wall)</b>				
C0 - D5 (m)	7.8	8.0	8.1	8.2
C90 - E4 (m)	6.2	6.6	6.9	7.1
<b>MLEDLP + DTX Diffuser (Ceiling)</b>				
C0 - D6.3 (m)	8.5	8.8	8.9	9.1
C90 - D5 (m)	7.8	8.0	8.1	8.2
<b>MLEDLP + D50A Diffuser (Wall)</b>				
C0 - D20 (m)	11.5	13.2	14.0	14.4
C90 - C40(m)	11.5	13.2	14.8	16.5

\*Refer to AS/NZ 2293 for complete spacing table.

# PREMIUM Exit and Emergency Luminaires

## Classic Options - Standard Diffusers

New DRX and DTX all-in-one diffusers now complete with all variations of pictogram and exit decals.

ACCESSORY	DESCRIPTION
DRX	Wall mount diffuser c/w decal pack
DTX	Ceiling mount diffuser c/w decal pack
D50A	Wall/ceiling mount translucent emergency diffuser



## Classic Options - Special Custom Diffusers

ACCESSORY	DESCRIPTION
BXA	Box style, four sided, ceiling mounted diffuser – EXIT (4 legends on each face to be specified)
RMBXA	Box style, four sided, ceiling mounted diffuser – RUNNING MAN (4 legends on each face to be specified)
DIF/SPECIAL	Other custom text screen printed diffusers



## Classic Options - Low Illuminance Exit Diffusers

DESCRIPTION	PART NUMBER						
Wall mounted	RM1/TM	RM2/TM	RM3/TM	X1A/TM	X2A/TM	X3A/TM	X4A/TM
Ceiling mount, single side	RMX1/TM	RMX2/TM	RMX3/TM	DS1A/TM	DS2A/TM	DS3A/TM	DS4A/TM
Ceiling mount, double side	RMD1/TM	RMD2/TM	RMD2/TM	DE1A/TM	DE2A/TM	DE3A/TM	DE4A/TM