

## CLEVERTRONICS LP WEATHERPROOF EXIT WALL MOUNT



### PRODUCT INFORMATION

Part Number	CWELED-WM-R
Description	LP Premium wall mounted IP66/67 weatherproof Exit, Enabled with Clevertest Plus
Construction	Base material: Polycarbonate Diffuser cover material: Polycarbonate
Mounting	Wall mount, Single-sided
Dimensions L x W x H	380mm x 190mm x 130mm
Weight	2.7kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running man (Must specify diffuser combination)
Lamp(s)	6 x High intensity LED, surface mounted onto a replaceable lamp bar - 100,000hour
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 5.1 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =E1.25 C <sub>90</sub> =E1
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	24m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550190	BATT:LP 3.2V 1500mAh 390mm lead, noBRKT.
8002335	PCA:CWELED Driver. #CT10164-L4.
8002120	PCA:DLED Cleverfit LightStrip,CT10152-D2

