

CLEVERTRONICS LP WEATHERPROOF SURFACE MOUNT WITH IP66/67 LAMP HEAD



PRODUCT INFORMATION

| | |
|-----------------------|---|
| Part Number | CLIFE-PRO-WP |
| MIC | AUT02320040001 |
| Description | LP Premium LifeLight Pro, high performance, surface mounted Emergency Light with IP66/67 head, Enabled with Clevertest plus |
| Construction | Polycarbonate |
| Mounting | Surface mount |
| Dimensions L x W x H | 232mm x 40mm x 40mm (Control pack) 122mm x 120mm x 75mm (Lamp head enclosure) |
| Weight | 1.4kg |
| Operating Mode | Non-maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery | Lithium Iron Phosphate, 3.2V 6400mAh |
| Charging Method | Intelligent current limited constant voltage |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 0.4 Watts (Standby), 2.7 Watts (Max) |
| IP Rating | IP66/67 (Lamp head only) |
| Operating Temperature | 1° to 40°C (Ambient) (Control Gear) -40° to 40°C (Lamp Head Assembly) |
| AS2293 Classification | C ₀ =D40 C ₉₀ =D40 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|----------------|---|
| 1550230 | BATT:LP 3.2V 6400mAh.200mm lead.Brkt. |
| CLIFE-PRO-CKIT | Lifelight Pro, Control Only, LP Lithium |
| 1100696 | Lifelight Pro, WP Head, Gen 2 |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order