

RCBO 1P+N 6kA C-6A 30mA type A

Similar image (Picture shows ADA910T)

Number of modules Number of poles 2 P Rated short circuit breaking capacity Icn AC according 6 kA IEC60898-1 Curve C Rated operational voltage Ue Rated current 6 A Rated residual operating current 30 mA Residual current type A Frequency So Hz Rated insulation voltage 2000 V Rated impulse withstand voltage Operating temperature -25 to 40 °C Electric endurance in number of cycles Number of mechanical operations 2 p C C C C C C C C C C C C C C
Rated short circuit breaking capacity Icn AC according 6 kA IEC60898-1 Curve C Rated operational voltage Ue 240 V Rated current 6 A Rated residual operating current 30 mA Residual current type A Frequency 50 Hz Rated insulation voltage Rated insulation voltage 6000 V Operating temperature -25 to 40 °C Electric endurance in number of cycles
Curve C Rated operational voltage Ue 240 V Rated current 6 A Rated residual operating current 30 mA Residual current type A Frequency 50 Hz Rated insulation voltage 2000 V Rated impulse withstand voltage 6000 V Operating temperature -25 to 40 °C Electric endurance in number of cycles 2000
Curve C C Rated operational voltage Ue 240 V Rated current 6 A Rated residual operating current 30 mA Residual current type A Frequency 50 Hz Rated insulation voltage 2000 V Rated impulse withstand voltage 6000 V Operating temperature -25 to 40 °C Electric endurance in number of cycles 2000
Rated operational voltage Ue Rated current 6 A Rated residual operating current 30 mA Residual current type A Frequency 50 Hz Rated insulation voltage 2000 V Rated impulse withstand voltage 6000 V Operating temperature -25 to 40 °C Electric endurance in number of cycles
Rated current 6 A Rated residual operating current 30 mA Residual current type A Frequency 50 Hz Rated insulation voltage 2000 V Rated impulse withstand voltage 6000 V Operating temperature -25 to 40 °C Electric endurance in number of cycles 2000
Rated residual operating current 30 mA Residual current type A Frequency 50 Hz Rated insulation voltage 2000 V Rated impulse withstand voltage 6000 V Operating temperature -25 to 40 °C Electric endurance in number of cycles 2000
Residual current type A Frequency 50 Hz Rated insulation voltage 2000 V Rated impulse withstand voltage 6000 V Operating temperature -25 to 40 °C Electric endurance in number of cycles 2000
Frequency 50 Hz Rated insulation voltage 2000 V Rated impulse withstand voltage 6000 V Operating temperature -25 to 40 °C Electric endurance in number of cycles 2000
Rated insulation voltage 2000 V Rated impulse withstand voltage 6000 V Operating temperature -25 to 40 °C Electric endurance in number of cycles 2000
Rated impulse withstand voltage 6000 V Operating temperature -25 to 40 °C Electric endurance in number of cycles 2000
Operating temperature -25 to 40 °C Electric endurance in number of cycles 2000
Electric endurance in number of cycles 2000
Number of mechanical operations 2000
The state of the s
Connection cross-sect. rigid cable 1 / 25mm ²
Connection cross-sect. flexible cable 1 / 16mm ²
Tightening torque 2,1Nm
Height of installed product 93 mm
Width of installed product 35 mm
Depth of installed product 68 mm
Standard text IEC 61009-1 ; AS/NZ 61009-1