



Main

| | |
|------------------------------------|---|
| Product brand | Clipsal |
| Range | Resi MAX |
| Product or component type | Comb busbar |
| Accessory / separate part category | Connection accessory |
| Poles description | 1P + N |
| Number of ways | 24, type : N + 1 L tooth connector(s) with 9 mm pitch |
| Distance between way | 18 mm |
| Total number of 18 mm modules | 24 |

Complementary

| | |
|--|------------------------------------|
| Insulation | Insulated |
| Device presentation | Cuttable |
| [Ie] rated operational current | 63 A (40 °C) |
| [Ue] rated operational voltage | 230 V AC Ph/N |
| [Ui] rated insulation voltage | 500 V AC conforming to IEC 61439-1 |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Mounting mode | Horizontal |
| Mounting location | Bottom on tunnel type terminals |
| 9 mm pitches | 48 |
| Width | 432 mm |
| Colour | White (RAL 9003) |

Environment

| | |
|------------------|---|
| standards | IEC 60947-7-1 IEC 61439-1 |
| fire resistance | 960 °C (30 s) conforming to IEC 60695-2-1 |
| pollution degree | 3 conforming to IEC 60947-7-1 |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1505 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |