18RU 600MM WIDE & 600MM DEEP

FULLY ASSEMBLED FREE STANDING SERVER CABINET

PART NUMBER: CBN-18RU-66FS BAR CODE: 9350784000996







Multiple cable entry glands at the top



Pre-installed lockable castors and stablising feet



Ample cable entry glands at the bottom



Nylon bush lining in all cable entry glands to protect from wear and tear



Earth straps on front and rear doors





Included roof fan kit



Earth bolt on side panel



Removable side panels

PRODUCT DESCRIPTION

Serveredge CBN-18RU-66FS fully assembled server racks are a perfect solution for securely storing your standard 19inch rack mount equipment. This free-standing rack has been especially designed for use with Servers, Switches, AV Equipment, Security Systems, Telephone Systems, Patch Panels and other Networking Equipment. This Serveredge rack is packed with features designed to simplify rack equipment installations and maintenance. The server rack comes with a 25-year manufacturer's warranty*.

GUARANTEE/WARRANTY

Serveredge products are manufactured at the highest standards using highest quality materials at an affordable price. Serveredge racks come with a 25-year Warranty. Subject to Serveredge Terms and Conditions*

PRODUCT INCLUDES

8 Way Horizontal PDU: (8) 3 Pin AUS GPO Output; (1) 3 Pin Aus Plug Input , 10A, 240V	× 1
2 Way Roof Mount Fan	× 1
Fixed Shelves (310mm Deep)	× 2
Lockable Castors	$\times 4$
Stabilizing Feet	$\times 4$
Adjustable 19inch Mounting Rails	$\times 4$
Keys	× 2
Heavy Duty M6 Cage Nuts, Washer & Screw	× 40
Split Perforated Mesh Door	× 1
Front Tempered Glass Door	× 1
Lockable Side Panels	× 2
Grounding Lugs - Front Door, Rear Door, Side Panels	

Earth Straps - Front Door & Rear Door

PRODUCT FEATURES

- Designed for IT, Audio Visual, Security and Data equipment
- Ships fully assembled for quick installation
- 1000Kg of stationary load capacity
- Pre-installed lockable castors
- Levelling feet extend to allow enclosure to be positioned on uneven floors and are removable when not required
- Convenient grounding system with grounding lugs on doors and side panels
- Earth straps on front and rear doors
- Built in baying tabs allow enclosures to be combined securely in rows (*Baying kit needs to be purchased separately)
- Includes (2) fixed shelves with 310mm depth
- Locking front glass door and rear split perforated mesh door
- Locking and removable side panels for easy access
- Nylon Bush lined cable entry glands at top and bottom to protect cables from wear and tear
- Conforms to Standard ANSI/EIA RS-31 -D, IEC297-2, DIN4191; PART1, DIN 4194;PAT7, GB/T3 47M 2-92*
- 25-year warranty* See T&Cs

PRODUCT SPECIFICATION

Rack Height	18RU
Shipping Dimensions (WDH/mm)	660 × 660 × 1000
Shipping weight (kg)	55
Unit Dimensions (WDH/mm)	600 × 600 × 988
Unit weight (kg)	53
Colour	Black
Weight Capacity - Stationary (kg)	1000
Grounding lug	Front and Back Door Frames
Fixed Shelves depth (mm)	310
Preset Mounting Distance (front to rear mounting rails) (mm)	315
Maximum Mounting Distance (front to rear mounting rails) (mm)	550
Minimum Mounting Distance (front to rear mounting rails) (mm)	145