



Platinum Range Surface Mount Spitfire 1 LED

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- LED energy efficient products.
- 10 year product design life.
- Lithium ion phosphate batteries.
- Advanced power management.



Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type	Emergency Lighting	Spitfire
Testing System		Single Point Unit
Operating Mode		Non-Maintained
Operating Voltage		240 VAC
Rated Frequency		50 Hz
Power Consumption		1.0 W
Mounting		Surface - Ceiling
LED Life		100,000 hours
Photometric Classification		C0:D40 C90:D40
Battery Type		LiFePO4
Height		68 mm
Width		167 mm
Depth		288 mm
Base Colour		White
Battery Replacement		0301301P
IP Rating		IP20
Standards Compliance		ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **SFB1LEDP**

PLATINUM RANGE SURFACE MOUNT SPITFIRE 1 LED

Stanilite Emergency and Exit Lighting > Platinum > Single Point Platinum > Platinum Spitfire EM



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: [Spitfire LED surface Mount Standard, Nexus LX, Nexus RF_ Installation Instructions](#)

User Manual: -

Manufacturer Datasheet: [Platinum Spitfire LED Surface Mount Non-maintained_ Manufacturer Datasheet](#)

Manufacturer Catalogue
& Product Selection: -