



main Victoria enclosure

VYMBV

Architecture

Intended door position	right
Fixing mode	surface-mounting

Functions

Ventilation	passive
-------------	---------

Compatibility

Cabinet profile measurement standard	metric
Suitable for lightning protection	no

Cover, door

Type of door closing	Latch
Identification od protection index	23
Interlockable	no
Cover type	Closed (plain)
Door lock can be sealed	no
Removable door	yes
Reversible door	no
Door leave	single
Door material	Metal
Door quantity	1
Symmetric doors (same width)	no
Cover type	none / closed
Door included	yes
Transparent cover or door	no

Materials

Colour	light grey
RAL colour	RAL 7035 - Light grey
Material	Steel
Material quality	Steel
Surface appearance	satin finish
Type of surface treatment	Painted

Dimensions

Insertion depth	278 mm
Depth of installed product	278 mm
Internal depth	276 mm
Height of installed product	688 mm
Width of installed product	488 mm
Thickness of sidewall material	1 mm

Installation, mounting

Suitable for ground mounting	yes
Suitable for wall mounting	no

Accessories included

Mounting plate included	no
-------------------------	----

Equipment

Quantity of rails	1
On/Off switch	no
Extension possible	no

Standards

Approvals	AS/NZS 61439-3
-----------	----------------

Safety

IK protection code against mechanical impacts	IK05
Protection index IP	IP23
Protection class	isol.class I
Glow wire test	according to AS/NZS 61439-1
Halogen free	no
Fire resistance	-