



### Main

|                                    |                             |
|------------------------------------|-----------------------------|
| Product or component type          | Appliance inlet             |
| Accessory / separate part category | Connection accessory        |
| Product compatibility              | Connector Easy56 EY56CSC315 |
| Plug, socket category              | Low voltage                 |
| Poles description                  | 1P + N + E                  |
| Pin number                         | 3 pins                      |
| Network type                       | AC                          |
| Outlet standard                    | Australian/New Zealand      |

### Complementary

|                                     |                         |
|-------------------------------------|-------------------------|
| Mounting mode                       | Surface mounted         |
| Plug, socket, control station shape | Straight                |
| [In] rated current                  | 15 A                    |
| [Ue] rated operational voltage      | 250 V                   |
| Network frequency                   | 50 Hz                   |
| Material                            | Polycarbonate cover :   |
| Contacts material                   | Brass pins :            |
| Connections - terminals             | Screw terminals         |
| Cable cross section                 | 1.5...6 mm <sup>2</sup> |
| Cable stiffness                     | Rigid or stranded       |
| Wire stripping length               | 10 mm                   |
| Product weight                      | 0.471 kg                |
| Height                              | 101 mm                  |
| Width                               | 101 mm                  |
| Depth                               | 102 mm                  |
| Colour                              | Grey ( RAL 7035 )       |

### Environment

|                                       |                             |
|---------------------------------------|-----------------------------|
| standards                             | AS/NZS 60320.1              |
| quality labels                        | RCM                         |
| IP degree of protection               | IP66 conforming to AS 60529 |
| ambient air temperature for operation | -25...75 °C                 |
| ambient air temperature for storage   | -25...75 °C                 |

### Offer Sustainability

|                          |                           |
|--------------------------|---------------------------|
| Sustainable offer status | Not Green Premium product |
|--------------------------|---------------------------|