



### Main

Product name	Easy56
Product or component type	Plug
Device short name	EY56P315
Plug, socket category	Low voltage
Poles description	1P + N + E
Pin number	3 pins
Shape of pin	Flat
Outlet standard	Australian/New Zealand

### Complementary

Plug, socket, control station shape	Straight
[In] rated current	15 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50 Hz
Material	Polycarbonate housing :
Contacts material	Brass pins :
Connections - terminals	Screw terminals
Cable cross section	1.5 mm <sup>2</sup>
Cable outer diameter	7.4...10.6 mm
Wire stripping length	12...34 mm
Cable entry	Cable gland
Thread type	M20
Product weight	0.107 kg
Height	67 mm
Width	67 mm
Depth	112.5 mm
Colour	Orange ( RAL 2004 ) plug Clear body

### Environment

standards	AS/NZS 3112
quality labels	RCM
IP degree of protection	IP66 conforming to AS 60529
ambient air temperature for operation	-25...75 °C
ambient air temperature for storage	-25...75 °C

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1539 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations