



### Main

Product name	Easy56
Device short name	EY56SW132
Product or component type	Switch
Poles description	1P
Control type	Rotary knob
Rotary handle padlocking	2 padlocks x Ø 8 mm

### Complementary

[Ue] rated operational voltage	250 V AC 50 Hz
[Uimp] rated impulse withstand voltage	2.5 kV conforming to IEC 60947-3 according to IEC 60947-3 conforming to IEC 60947-3 IEC 60947-3 conforming to IEC 60947-3 conforming to IEC 60947-3 IEC 60947-3 2.5 kV conforming to AS/NZS 3133 according to AS/NZS 3133 conforming to AS/NZS 3133 AS/NZS 3133 conforming to AS/NZS 3133 conforming to AS/NZS 3133 AS/NZS 3133
[Ithe] conventional enclosed thermal current	32 A
[Ie] rated operational current	32 A AC-21A at 250 V AC 32 A AC-23A at 250 V AC
Making capacity	320 A at 250 V AC-21A 320 A at 250 V AC-23A
[Icm] rated short-circuit making capacity	1 kA at 250 V (AC-21A) 1 kA at 250 V (AC-23A)
[Icw] rated short-time withstand current	1.5 kA at 250 V duration: 1 s
Breaking capacity	0.2 kA at 250 V (AC-21A) 0.2 kA at 250 V (AC-23A)
Suitability for isolation	Yes
Connections - terminals	Screw terminals cable 1...16 mm <sup>2</sup> - cable stiffness: rigid or stranded -
Height	101 mm
Width	101 mm
Depth	101 mm
Product weight	0.471 kg
Colour	Grey RAL 7035 body Dark grey rotary handle

### Environment

standards	AS/NZS 3133
IP degree of protection	IP66 conforming to AS 60529
ambient air temperature for operation	-25...75 °C

### Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.