Catalogue No: **ECLEM22LM**

ECONOMY E-LUNA CIRCULAR LED IP20 EM 2200Im MAINTAINED

Stanilite Emergency and Exit Lighting > Economy > Single Point Economy > Economy Circluar EM





Economy E-Luna Circular LED IP20 Em 2200 lumens Maintained

- Compliance to latest ASNZS2293.3:2018.
- LED technology.
- Extensive Range.
- Colour temperature 4,000K.
- High colour rendering index CRI >80.

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Emergency Lighting	Circular
Testing System	Single Point Unit
Operating Mode	Maintained
Operating Voltage	240 VAC
Rated Frequency	50 Hz
Power Consumption	31.0 W
Mounting	Surface - Universal
LED Life	50,000 hours
Lumen Output	2200 lumens
Photometric Classification	C0:D32 C90:D32
Battery Type	Ni-Cd
Height	85 mm
Width	325 mm
Depth	325 mm
Base Colour	White
Diffuser Colour	Opaque
Battery Replacement	0301016P
IP Rating	IP20
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005



Catalogue No: **ECLEM22LM**

ECONOMY E-LUNA CIRCULAR LED IP20 EM 2200Im MAINTAINED

Stanilite Emergency and Exit Lighting > Economy > Single Point Economy > Economy Circluar EM



REFERENCES	
IECEx Certificate	
Supplier Declaration of Conformity:	ELUNA IP20 LED Circular, NiCad Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	Economy e-Luna Circular LED AC, Emergency_Installation Instructions
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

