

# DETAIL

## 9 Watt, adjustable, narrow beam LED downlight

DETAIL is available in black or white bevelled trim and you can adjust the direction of its narrow beam (60°) to light specific areas.



ADJUSTABLE DOWNLIGHTS

- Sealed ring housing on IP65 models keeps ceilings airtight
- High luminous efficacy
- Good glare control
- Flex and plug for fast installation
- Robust diecast aluminium construction

### Applications

Residential, bathrooms, hospitality, offices



**60°**  
Beam Angle



**0-30°**  
Adjustment Angle



**>80**  
CRI Colour Rendering Index



**5yr**  
Warranty



**50,000hr**  
Expected Lifetime



**DIM**  
Phase Cut Dimmable



**IC-4**  
Covered & Abutted

WATT	LUMEN	lm/W	TRIM	CCT	WEIGHT	IP	SAP CODE	PROD CODE
9W	890lm	99lm/W	BLACK	3000K	0.4kg	IP65	2000584	<b>D9W110R3KBKIP65</b>
9W	890lm	99lm/W	WHITE	3000K	0.4kg	IP65	2000159	<b>D9W110R3KWIP65</b>
9W	940lm	104lm/W	BLACK	4000K	0.4kg	IP65	2000160	<b>D9W110R4KBKIP65</b>
9W	940lm	104lm/W	WHITE	4000K	0.4kg	IP65	2000161	<b>D9W110R4KWIP65</b>
9W	980lm	109lm/W	BLACK	5000K	0.4kg	IP65	2000585	<b>D9W110R5KBKIP65</b>
9W	980lm	109lm/W	WHITE	5000K	0.4kg	IP65	2000164	<b>D9W110R5KWIP65</b>
9W	1000lm	111lm/W	WHITE	3000K	0.4kg	IP20	2000836	<b>D9W110R3KWIP20</b>
9W	1080lm	120lm/W	WHITE	4000K	0.4kg	IP20	2000837	<b>D9W110R4KWIP20</b>
9W	1060lm	118lm/W	WHITE	5000K	0.4kg	IP20	2000838	<b>D9W110R5KWIP20</b>

