

CLEVERTRONICS LP LIFELIGHT



PRODUCT INFORMATION

Part Number	CLIFE-ZW
Description	LP Premium Lifelight, high performance, recessed Emergency Light
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single mint LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 3.9 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
CLIFE-CKIT	Lifelight, Control Only, LP Lithium
1100930	Lifelight Head Assembly, Round, 1LED
8001450	PCA:Powerline Node ZW, #CT10310-A6

