



FLEXI 24V WHITE COLOUR FLH2420 - 20W/M


Roll length 5m, maximum run length 5m, 24V, high output LED Strip, IP20, strip width 10mm.

Application

A creative solution for residential and commercial interior spaces

Design Specifications

- High output greater than 1700lm/m
- High efficiency LED optics with self adhesive tape
- Maximum run length 5 m, cuttable every 62.5 mm at the scissors symbol ✂
- Heat sink required for system performance and 24V constant voltage LED driver required
- **Dimming options:** ([quick link](#))
Type A - Trailing edge dimming,
Type B - LED strip controller LT8915DIM/BT with LT8914DIM/RP if required,
Type C - Analogue 1-10V
Type D - DALI 2 control
- **LED channel options** ([quick link](#))




Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **refer dimming options**



Technical Specification

Product	Model No.	Input Voltage (V/DC)	Watts per metre (W/m)	Beam Angle (°)	CRI	Lumens (lm)
	FLH2420 WW	24	20	115	80	1700
	FLH2420 CW	24	20	115	80	1800
	FLH2420 DL	24	20	115	80	2000
	FLH2420WW/5M	24	20	115	80	1700
	FLH2420CW/5M	24	20	115	80	1800
	FLH2420DL/5M	24	20	115	80	2000

LEDs Per Metre	Cutting Interval	CCT (K)	Body Colour	Dim (mm)
96	62.5	3000	CLEAR	1000(L) x 10(W) x 2(H)
96	62.5	4000	CLEAR	1000(L) x 10(W) x 2(H)
96	62.5	6000	CLEAR	1000(L) x 10(W) x 2(H)
96	62.5	3000	CLEAR	5000(L) x 10(W) x 2(H)
96	62.5	4000	CLEAR	5000(L) x 10(W) x 2(H)
96	62.5	6000	CLEAR	5000(L) x 10(W) x 2(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

