

PRODUCT DATASHEETSPC.T CL 25 W 230 V E14

SPECIAL T | Incandescent lamps, tubular shape







TECHNICAL DATA

Electrical data

Rated wattage	25.00 W
Nominal wattage	25.00 W
Power factor λ	1.00


Photometrical data

Nominal luminous flux	160 lm
Rated luminous flux	160 lm
Rated color temperature	2700 K
Color temperature	2700 K
Luminous flux	160 lm
Color rendering index Ra	100
Color rendering index Ra	100

Light technical data

Starting time	0.0 s
Warm-up time (60 %)	0.00 s

Dimensions & weight



Diameter	26.0 mm
Overall length	55.0 mm
Outer bulb	T26
Light center length (LCL)	45.0 mm
Length with base excl. base pins/connection	57.00 mm
Length	55.0 mm

Lifespan

Nominal lamp life time	1000 h

Rated lamp life time	1000 h

Additional product data

Base (standard designation)	E14	
Mercury content	0.0 mg	
Mercury-free	Yes	

Capabilities

Dimmable	Yes

Certificates & standards

Energy efficiency class	Е
Energy consumption	25 kWh/1000h

Country-specific categorizations

ILCOS	IBT/C-25-230-E14-26

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300309637	SPC.T CL 25 W 230 V E14	Shipping carton box 100	285 mm x 140 mm x 150 mm	5.99 dm³	1301.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.