



Pan-Steel® MLTFC4H-LP316 Cable Tie, PET Coated SS 316, Black, Heavy, 4" Dia.

MLTFC4H-LP316

The MLTFC4H-LP316 self-locking cable tie speeds up installation with a unique self-locking head design that locks into place at any part of the tie body. The 316 stainless steel is wrapped in UV-resistant, halogen-free, Polyester to promote worker safety and reliability in corrosive, high-vibration, temperature-extreme environments. The Polyester coating is available in six color options and provides visual indication for easy identification in color-coding applications.

Specifications

Product Type	Cable Tie
Sub Brand	Pan-Steel®
Color	Black
Environment	Harsh
Material	Stainless Steel Type 316
Finish/Coating	Polyester Fully-Coated
Resistance Properties	UV-Resistant
Overall Length (In.)	14.3
Overall Length (mm)	362
Body Width (In.)	0.319
Body Width (mm)	8.1
Body Thickness (In.)	0.017
Body Thickness (mm)	0.4
Maximum Bundle Diameter (In.)	4
Maximum Bundle Diameter (mm)	102
Minimum Bundle Diameter (In.)	0.5
Minimum Bundle Diameter (mm)	12.7
Minimum Loop Tensile Strength (N)	1112
Minimum Loop Tensile Strength (lb)	250
Maximum Operating Temperature (°C)	150
Maximum Operating Temperature (°F)	302
Minimum Operating Temperature (°C)	-40
Minimum Operating Temperature (°F)	-40
Minimum Installation Temperature (°C)	-40
Minimum Installation Temperature (°F)	-40

Specifications (continued)

Standards Met	ABS,CE,UL
For Use With	GS4MT-E, PBTMT, PPTMT, ST2MT, HTMT
Application	Harsh Environment
Part Features	Self-locking head, 316 base stainless steel, polyester coated, UV resistant, Halogen Free, 0.31 wide

Packaging Detail

UPC	07498359325
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0238
Std. Ctn. Qty.	250
Std. Ctn. Volume (cf)	0.1191