



### Main

Range	Clipsal Iconic
Product or component type	Grid plate
Device presentation	Grid plate
Outlet poles configuration	1P + E with shutter
Provided equipment	Screws Grid plate
Fixing mode	By screws (horizontal)
Type of packing	Polybag
Quantity per set	Set of 10
Sale per indivisible quantity	1
Rated current	15 A, 250 V AC, 50 Hz

### Complementary

Number of power socket outlets	1
Device mounting	Flush
Outlet standard description	With earthing contact
Outlet standard	Australian/New Zealand
Ground lug position	Straight 180° position
Colour tint	Vivid white (VW)
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Electrical durability	10000 cycles
Connections - terminals	3 x screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Number of cables	1...4
Clamping connection capacity	2.5 mm <sup>2</sup> (stranded) 2.5 mm <sup>2</sup> (flexible) 2.5 mm <sup>2</sup> (rigid)
Wire stripping length	16 mm
Material	PC (polycarbonate) for grid plate PP (polypropylene) for flaps POM (polyoxymethylene) for shutter
Height	115 mm
Width	71 mm
Depth	31 mm
Embedding depth	23 mm
Product weight	0.82 kg
Standards	AS/NZS 3112

### Environment

product certifications	RCM
------------------------	-----

### Offer Sustainability

Sustainable offer status	Not Green Premium product
REACH	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.