# 3015/20G

# Clipsal Iconic - switched socket - 20 A





#### Main

Range	Clipsal Iconic
Product or component type	Switched socket
Device presentation	Mechanism with fixing frame
Outlet poles configuration	2P + E
Type of packing	Polybag
Quantity per set	Set of 10
Sale per indivisible quantity	1
Rated current	20 A, 250 V AC, 50 Hz

## Complementary

Number of power socket outlets	1	
Device mounting	Flush	
Number of rocker	1	
Outlet standard	Australian	
Outlet standard description	With earthing contact	
Outlet standard	Australian/New Zealand	
Ground lug position	Straight 180° position	
Fixing mode	By screw	
Installation direction	Horizontal	
Surface finish	Matt	
Ambient air temperature for operation	045 °C	
Relative humidity	1095 %	
Electrical durability	9000 cycles	
Connections - terminals	3 x screw terminals	
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)	
Clamping connection capacity	1 x 2.54 x 2.5 mm² (rigid) 1 x 2.54 x 2.5 mm² (stranded) 1 x 2.54 x 2.5 mm² (flexible)	
Wire stripping length	16 mm	
Material	PC (polycarbonate) for fixing frame PP (polypropylene) for rocker	
Height	115 mm	
Width	71 mm	
Depth	31 mm	
Embedding depth	23 mm	
Product weight	0.82 kg	
Standards	AS/NZS 3112	

### **Environment**

product certifications RCM	
----------------------------	--

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1817 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold

Need no specific recycling operations

