



### Main

Range	Clipsal Iconic
Product or component type	Socket
Device presentation	Grid plate with skin
Outlet poles configuration	1P + E with shutter
Provided equipment	Screws Grid plate Skin
Fixing mode	By screws (horizontal)
Type of packing	Polybag
Quantity per set	Set of 10
Sale per indivisible quantity	1
Rated current	10 A, 250 V AC, 50 Hz

### Complementary

Number of power socket outlets	1
Device mounting	Flush
Outlet standard description	With earthing contact
Outlet standard	Australian/New Zealand
Ground lug position	Straight 180° position
Colour tint	Vivid white (VW)
Surface finish	Matt
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Electrical durability	12000 cycles
Connections - terminals	3 x screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Number of cables	1...4
Clamping connection capacity	2.5 mm <sup>2</sup> (stranded) 2.5 mm <sup>2</sup> (flexible) 2.5 mm <sup>2</sup> (rigid)
Wire stripping length	16 mm
Material	PC (polycarbonate) for grid plate PP (polypropylene) for flaps POM (polyoxymethylene) for shutter PC (polycarbonate) for skin ABS (acrylonitrile butadiene-styrene) for skin
Height	120 mm
Width	78 mm
Depth	36 mm
Embedding depth	24 mm
Product weight	0.1 kg
Standards	AS/NZS 3112

### Environment

product certifications	RCM
------------------------	-----

### Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

