



Main

| | |
|-------------------------------|------------------------|
| Range | Clipsal Iconic |
| Product or component type | Grid plate |
| Device presentation | Grid plate |
| Outlet poles configuration | 1P + E with shutter |
| Provided equipment | Screws Grid plate |
| Fixing mode | By screws (horizontal) |
| Type of packing | Polybag |
| Quantity per set | Set of 10 |
| Sale per indivisible quantity | 1 |
| Rated current | 10 A, 250 V AC, 50 Hz |

Complementary

| | |
|---------------------------------------|---|
| Number of power socket outlets | 1 |
| Device mounting | Flush |
| Outlet standard description | With earthing contact |
| Outlet standard | Australian/New Zealand |
| Ground lug position | Straight 180° position |
| Colour tint | Vivid white (VW) |
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 10...95 % |
| Electrical durability | 12000 cycles |
| Connections - terminals | 3 x screw terminals |
| Screwdriver shape | Philips No 2 Square drive no 1 (SQ1) |
| Number of cables | 1...4 |
| Clamping connection capacity | 2.5 mm ² (stranded) 2.5 mm ² (flexible) 2.5 mm ² (rigid) |
| Wire stripping length | 16 mm |
| Material | PC (polycarbonate) for grid plate PP (polypropylene) for flaps POM (polyoxymethylene) for shutter |
| Height | 115 mm |
| Width | 71 mm |
| Depth | 26 mm |
| Embedding depth | 18 mm |
| Product weight | 0.094 kg |
| Standards | AS/NZS 3112 |

Environment

| | |
|------------------------|-----|
| product certifications | RCM |
|------------------------|-----|

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| REACH | Reference not containing SVHC above the threshold |