

3025USB2-VW

Iconic - Double switched GPO (grid + skin) 10A 250V
with twin 2.1A USB charger module



Main

Range	Clipsal Iconic
Product or component type	USB charger + socket-outlet
Device presentation	Grid plate with skin
Outlet poles configuration	1P + E with shutter
Fixing mode	By screw

Complementary

Socket number	2
Device mounting	Flush
Provided equipment	USB charger
Outlet standard description	With earthing contact
Outlet standard	Australian/New Zealand
Ground lug position	Straight 180° position
Mounting mode	Horizontal
Colour tint	Vivid white (VW)
Surface finish	Matt
Type of packing	Polybag
Quantity per set	Set of 10
Sale per indivisible quantity	1
Ambient air temperature for storage	0...60 °C
Rated current	10 A for socket
[Ue] rated operational voltage	250 V AC 50 Hz
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Service life in cycles	12000 cycles
Electrical durability	12000 cycles
Connections - terminals	Screw terminal
Number of terminals	3
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Number of cables	1...4
Clamping connection capacity	2.5 mm ² (stranded) 2.5 mm ² (flexible) 2.5 mm ² (rigid)
Wire stripping length	16 mm
Material	PC (polycarbonate) for grid plate PP (polypropylene) for flaps POM (polyoxymethylene) for shutter PC (polycarbonate) for skin ABS (acrylonitrile butadiene-styrene) for skin POM (polyoxymethylene) for locking bar
Height	120 mm
Width	78 mm
Depth	44 mm
Standards	AS/NZS 60950-1 AS/NZS 3112

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

product certifications

RCM
