

## 3025XAG

Iconic - Double switched GPO (grid less skin) 10A  
250V with 10AX 2way switch



### Main

Range	Clipsal Iconic
Product or component type	Switch and socket-outlet
Device presentation	Grid plate with switch
Outlet poles configuration	1P + E with shutter
Fixing mode	By screw

### Complementary

Socket number	2
Device mounting	Flush
Outlet standard description	With earthing contact
Outlet standard	Australian/New Zealand
Ground lug position	Straight 180° position
Switch function	2-way
Mounting mode	Horizontal
Colour tint	White
Surface finish	Matt
Type of packing	Polybag
Quantity per set	Set of 10
Sale per indivisible quantity	1
Ambient air temperature for storage	0...60 °C
Rated current	10 A for socket 10 AX for switch
[Ue] rated operational voltage	250 V AC 50 Hz
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Service life in cycles	12000 cycles
Electrical durability	12000 cycles
Connections - terminals	Screw terminal
Number of terminals	3
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Number of cables	1...4
Clamping connection capacity	2.5 mm <sup>2</sup> (stranded) 2.5 mm <sup>2</sup> (flexible) 2.5 mm <sup>2</sup> (rigid)
Wire stripping length	16 mm
Material	PC (polycarbonate) for grid plate PP (polypropylene) for flaps POM (polyoxymethylene) for shutter PC (polycarbonate) for switch PA66 for switch POM (polyoxymethylene) for locking bar
Height	115 mm
Width	71 mm
Depth	31 mm
Product weight	0.071 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Standards

AS/NZS 3112  
AS/NZS 3133  
AS/NZS 60669.1

---

## Environment

---

product certifications

RCM

---

## Offer Sustainability

---

Sustainable offer status

Not Green Premium product

---

REACH

Reference not containing SVHC above the threshold

---