## 3041AL-VW

## Iconic - 1gang architrave switch assembly 10AX 250V vivid white

ľ				
	(	_	1	
ı				

Main	
Range	Clipsal Iconic
Product or component type	Switch
Device presentation	Complete switch
Provided equipment	Screws Switch Grid plate Skin LED
Device application	Lighting
Fixing mode	By screws
Colour tint	Vivid white (VW)
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Rated current	10 AX - 250 V AC, 50 Hz
Light source	LED 60 mW

## Complementary

Complementary	
Device mounting	Flush
Switch function	1/2-way
Number of gangs	1 gang vertical 79 mm
Number of rocker	1
Actuator	Rocker
Surface finish	Matt
Surface treatment	Untreated
Ambient air temperature for storage	060 °C
Motor M-rating AS3133	M80
Load type	Inductive Inductive Light Fluorescent lamp
Dielectric strength	20000 V
Ambient air temperature for operation	045 °C
Relative humidity	1095 %
Electrical durability	20000 cycles, conforming to AS/NZS 60669
Connections - terminals	4 x screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	1.5 mm² (stranded) 1.5 mm² (flexible) 1.5 mm² (rigid)
Wire stripping length	10 mm
Local signalling	LED warm white optional LED warm white locator LED warm white indicator
Material	Grid plate: PC (polycarbonate) Skin: PC (polycarbonate) Skin: ABS (acrylonitrile butadiene-styrene) Flaps: PP (polypropylene) Housing: PC (polycarbonate) Housing: PA66 Locking bar: POM (polyoxymethylene)

Height	113 mm		
Width	38 mm		
Depth	40 mm		
Product weight	0.076 kg		
Environment			
product certifications	RCM		
Offer Sustainability			
Sustainable offer status	Not Green Premium product		
REACh	Reference not containing SVHC above the threshold		

