

## 3042AL-VW

Iconic - 2gang architrave switch assembly with white LED 10AX 250V vivid white



### Main

Range	Clipsal Iconic
Product or component type	Switch
Device presentation	Complete switch
Provided equipment	Screws Switch Grid plate Skin LED
Device application	Lighting
Fixing mode	By screws
Colour tint	Vivid white (VW)
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Rated current	10 AX - 250 V AC, 50 Hz
Light source	LED 60 mW

### Complementary

Device mounting	Flush
Switch function	1/2-way
Number of gangs	2 gangs vertical 79 mm
Number of rocker	2
Actuator	Rocker
Surface finish	Matt
Surface treatment	Untreated
Ambient air temperature for storage	0...60 °C
Motor M-rating AS3133	M80
Load type	Inductive Inductive Light Fluorescent lamp
Dielectric strength	20000 V
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Electrical durability	20000 cycles, conforming to AS/NZS 60669
Connections - terminals	4 x screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	1.5 mm <sup>2</sup> (stranded) 1.5 mm <sup>2</sup> (flexible) 1.5 mm <sup>2</sup> (rigid)
Wire stripping length	10 mm
Local signalling	LED warm white optional LED warm white locator LED warm white indicator
Material	Grid plate : PC (polycarbonate) Skin : PC (polycarbonate) Skin : ABS (acrylonitrile butadiene-styrene) Flaps : PP (polypropylene) Housing : PC (polycarbonate) Housing : PA66 Locking bar : POM (polyoxymethylene)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Height	113 mm
Width	38 mm
Depth	39 mm
Product weight	0.05 kg

## Environment

product certifications	RCM
------------------------	-----

## Offer Sustainability

Sustainable offer status	Not Green Premium product
REACH	Reference not containing SVHC above the threshold