

## 3045VA-VW

Iconic - 5gang vert switch assembly 10AX 250V vivid white



### Main

|                               |  |
|-------------------------------|--|
| Range                         | Clipsal Iconic                         |
| Product or component type     | Switch                                 |
| Device presentation           | Complete switch                        |
| Provided equipment            | Screws<br>Switch<br>Grid plate<br>Skin |
| Device application            | Lighting                               |
| Fixing mode                   | By screws                              |
| Colour tint                   | Vivid white (VW)                       |
| Type of packing               | Polybag                                |
| Quantity per set              | Set of 20                              |
| Sale per indivisible quantity | 1                                      |
| Rated current                 | 10 AX - 250 V AC, 50 Hz                |

### Complementary

|                                       |  |
|---------------------------------------|--|
| Device mounting                       | Flush  |
| Switch function                       | 1/2-way  |
| Number of gangs                       | 5 gangs vertical 84 mm   |
| Number of rocker                      | 5  |
| Actuator                              | Rocker   |
| Surface finish                        | Matt   |
| Surface treatment                     | Untreated  |
| Ambient air temperature for storage   | 0...60 °C  |
| Motor M-rating AS3133                 | M80  |
| Load type                             | Inductive<br>Inductive<br>Light<br>Fluorescent lamp  |
| Dielectric strength                   | 20000 V  |
| Ambient air temperature for operation | 0...45 °C  |
| Relative humidity                     | 10...95 %  |
| Electrical durability                 | 20000 cycles, conforming to AS/NZS 60669   |
| Connections - terminals               | 4 x screw terminals  |
| Screwdriver shape                     | Philips No 2<br>Square drive no 1 (SQ1)  |
| Clamping connection capacity          | 1.5 mm <sup>2</sup> (stranded)<br>1.5 mm <sup>2</sup> (flexible)<br>1.5 mm <sup>2</sup> (rigid)  |
| Wire stripping length                 | 10 mm  |
| Material                              | Grid plate : PC (polycarbonate)<br>Skin : PC (polycarbonate)<br>Skin : ABS (acrylonitrile butadiene-styrene)<br>Flaps : PP (polypropylene)<br>Housing : PC (polycarbonate)<br>Housing : PA66<br>Locking bar : POM (polyoxymethylene) |
| Height                                | 120 mm   |
| Width                                 | 78 mm  |
| Depth                                 | 39 mm  |
| Product weight                        | 0.138 kg   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

---

product certifications

RCM

---

---