3046HA-VW

Iconic - 6gang horiz switch assembly 10AX 250V vivid white



| Main | |
|-------------------------------|--|
| Range | Clipsal Iconic |
| Product or component type | Switch |
| Device presentation | Complete switch |
| Provided equipment | Screws Switch Grid plate Skin |
| Device application | Lighting |
| Fixing mode | By screws |
| Colour tint | Vivid white (VW) |
| Type of packing | Polybag |
| Quantity per set | Set of 20 |
| Sale per indivisible quantity | 1 |
| Rated current | 10 AX - 250 V AC, 50 Hz |

| Complementary | |
|---------------------------------------|---|
| Device mounting | Flush |
| Switch function | 1/2-way |
| Number of gangs | 6 gangs horizontal 84 mm |
| Number of rocker | 6 |
| Actuator | Rocker |
| Surface finish | Matt |
| Surface treatment | Untreated |
| Ambient air temperature for storage | 060 °C |
| Motor M-rating AS3133 | M80 |
| Load type | Inductive Inductive Light Fluorescent lamp |
| Dielectric strength | 20000 V |
| Ambient air temperature for operation | 045 °C |
| Relative humidity | 1095 % |
| Electrical durability | 20000 cycles, conforming to AS/NZS 60669 |
| Connections - terminals | 4 x screw terminals |
| Screwdriver shape | Philips No 2 Square drive no 1 (SQ1) |
| Clamping connection capacity | 1.5 mm² (stranded) 1.5 mm² (flexible) 1.5 mm² (rigid) |
| Wire stripping length | 10 mm |
| Material | Grid plate: PC (polycarbonate) Skin: PC (polycarbonate) Skin: ABS (acrylonitrile butadiene-styrene) Flaps: PP (polypropylene) Housing: PC (polycarbonate) Housing: PA66 Locking bar: POM (polyoxymethylene) |
| Height | 120 mm |
| Width | 78 mm |
| Depth | 39 mm |
| Product weight | 0.152 kg |

Environment

| product certifications | RCM |
|------------------------|-----|
| | |

