



Main

Range	Clipsal Iconic
Product or component type	Switch mechanism
Device presentation	Mechanism
Provided equipment	Switch
Device application	Lighting
Fixing mode	Locking bar
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Rated current	20 A/16 AX - 250 V AC, 50 Hz

Complementary

Switch function	1/2-way
Ambient air temperature for storage	0...60 °C
Motor M-rating AS3133	M80
Load type	Inductive Inductive Light Fluorescent lamp
Dielectric strength	20000 V
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Electrical durability	20000 cycles, conforming to AS/NZS 60669
Connections - terminals	4 x screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	1.5 mm ² (stranded) 1.5 mm ² (flexible) 1.5 mm ² (rigid)
Wire stripping length	10 mm
Material	Housing : PC (polycarbonate) Housing : PA66
Height	23 mm
Width	23 mm
Depth	32 mm
Product weight	0.016 kg

Environment

product certifications	RCM
------------------------	-----

Offer Sustainability

Sustainable offer status	Not Green Premium product
REACH	Reference not containing SVHC above the threshold